

KODSAN ELEKTRİKLİ BOYLER



A)BOYUT TABLOSU

Model		100	160	200	350	500	600	800	1000	1500	2000
Hacim	lt	100	160	200	350	500	600	800	1000	1500	2000
Çap	mm	490	590	590	750	750	750	900	1000	1260	1260
Yükseklik	mm	1100	1140	1335	1405	1830	2065	2140	2080	1890	2270
Tesisat bağlantı		1"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
Sirkülasyon		3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	1"	1"	1 1/4"	1 1/4"
Boş ağırlık	kg	50	69	80	115	146	165	235	269	342	399

B)ENERJİ TABLOSU

ÜRÜN	Kapasite kg/h(kCal/h)	ÜRÜN	Kapasite kg/h(kCal/h)	ÜRÜN	Kapasite kg/h(kCal/h)
1 X 2 kW	49 (1720)	2 X 7,5 kW	369 (12900)	4 X 7,5 kW	737 (25800)
1 X 3 kW	74 (2580)	2 X 10 kW	491 (17200)	4 X 10 kW	983 (34400)
1 X 4 kW	98 (3440)	2 X 12 kW	590 (20640)	4 X 12 kW	1179 (41280)
1 X 5 kW	123 (4300)	2 X 15 kW	737 (25800)	4 X 15 kW	1474 (51600)
1 X 6 kW	147 (5160)	3 X 3 kW	221 (7740)	5 X 10 kW	1229 (43000)
1 X 7,5 kW	184 (6450)	3 X 5 kW	369 (12900)	5 X 12 kW	1474 (51600)
1 X 10 kW	246 (8600)	3 X 6 kW	442 (15480)	5 X 15 kW	1843 (64500)
1 X 15 kW	369 (12900)	3 X 7,5 kW	553 (19350)	6 X 6 kW	885 (30960)
2 X 3 kW	147 (5160)	3 X 8 kW	590 (20640)	6 X 12 kW	1769 (61920)
2 X 4 kW	197 (6880)	3 X 10 kW	737 (25800)	6 X 15 kW	2211 (77400)
2 X 5 kW	246 (8600)	3 X 12 kW	885 (30960)	7 X 15 kW	2580 (90300)
2 X 6 kW	295 (10320)	3 X 15 kW	1106 (38700)		

Kapasite (kg/h) 10/45°C çalışma şartları içindir.